

PAR-WT60R-E / PAR-WR61R-E

Wireless Remote Transmitter /
Wireless Remote Receiver

Key Features:

- Flat panel design
- Wireless connectivity
- Auto adaptive control logic
- Touch buttons with user friendly icons
- Backlit display screen

Key Benefits:

- Stylish and modern aesthetics
- Remote control from any room
- System regulation for optimal efficiency
- Intuitive operation
- Easy to navigate



PAR-WT60R-E



PAR-WR61R-E



ecodan[®]
Renewable Heating Technology

Heating Product Information

PAR-WT60R-E / PAR-WR61R-E Wireless Remote Transmitter / Wireless Remote Receiver




MODEL	PAR-WT60R-E	PAR-WR61R-E
Description	FTC Wireless Controller Transmitter	FTC Wireless Controller Receiver
Max Number of Units per System	8	1
Power Supply	2 x AA Batteries	FTC
Dimensions (mm)		
Width	100	100
Depth	23	30
Height	100	80
Weight (kg)	0.14	0.15
Installation Location	Free-Standing or Wall-Mounted	Wall-Mounted
Display	Backlit LED Screen	N/A
Control		Set Temperature Forced Domestic Hot Water (DHW) Holiday Mode
Monitor		Room Temperature Set Room Temperature Forced Domestic Hot Water (DHW) Smart Grid Holiday Mode Error

PAR-WT60R-E DIMENSIONS

PAR-WR61R-E DIMENSIONS

All dimensions (mm)



Telephone: 01707 282880
email: heating@meuk.mee.com
ecodan.co.uk



UNITED KINGDOM Mitsubishi Electric Europe Living Environment Systems Division, Travellers Lane, Hatfield, Hertfordshire, AL10 8XB, England. Telephone: 01707 282880 Fax: 01707 278881
IRELAND Mitsubishi Electric Europe, Westgate Business Park, Ballymount, Dublin 24, Ireland. Telephone: (01) 419 8800 Fax: (01) 419 8890 International code: (003531)

Country of origin: United Kingdom - Japan - Thailand - Malaysia. ©Mitsubishi Electric Europe 2023. Mitsubishi and Mitsubishi Electric are trademarks of Mitsubishi Electric Europe B.V. The company reserves the right to make any variation in technical specification to the equipment described, or to withdraw or replace products without prior notification or public announcement. Mitsubishi Electric is constantly developing and improving its products. All descriptions, illustrations, drawings and specifications in this publication present only general particulars and shall not form part of any contract. All goods are supplied subject to the Company's General Conditions of Sale, a copy of which is available on request. Third-party product and brand names may be trademarks or registered trademarks of their respective owners.

Note: Refer to 'Installation Manual' and 'Instruction Book' for further 'Technical Information'. The fuse rating is for guidance only and please refer to the relevant databook for detailed specification. It is the responsibility of a qualified electrician/electrical engineer to select the correct cable size and fuse rating based on current regulation and site specific conditions. Mitsubishi Electric's air conditioning equipment and heat pump systems contain a fluorinated greenhouse gas, R410A (GWP:2088), R32 (GWP:675), R407C (GWP:1774), R134a (GWP:1430), R513A (GWP:631), R454B (GWP:466), R1234ze (GWP:7) or R1234yf (GWP:4). *These GWP values are based on Regulation (EU) No 517/2014 from IPCC 4th edition. In case of Regulation (EU) No.626/2011 from IPCC 3rd edition, these are as follows. R410A (GWP:1975), R32 (GWP:550), R407C (GWP:1650) or R134a (GWP:1300).

Effective as of August 2023

